


IRIS

Antiglare Modular - Dim to Warm



FX

ARC SERIES



Baffle Colour Selection

Choose from additional White, Gold or Silver Baffle covers

Easy Installation

Mains Loop-in and Loop-out Driver feature on Standard & Mains Dimmable Models

High CRI & Antiglare

A set back reflector for a low glare rating coupled with a powerful & Crisp light engine to help enhance the appearance of colours & objects

Description

The IRIS Antiglare Dim to Warm is our versatile and yet elegant Fire Rated LED Downlight, featuring a multitude of Beam Angles, Power Outputs, Kelvin and Dimming Protocol variations. This unit has been designed with Antiglare at the forefront of its design with its set back reflector, offering a UGR of only 11 when ordered with a black insert and 19 in standard white; producing a low glare and superior visual comfort. At a Colour rendering Index (CRI) of 95+ the IRIS offers as a crisp light in any output which in turn enhances the appearance of colours and objects it comes into contact with.

Dimensions

Height: 81mm
Diameter: 80mm
Cut Out: 68-70mm

Wattage	10W	12W
Lumen Output	700lm	840lm
Lumens per Watt	70lm/w	
Finish	RAL 9003	
Class	Class 3	

Part code Builder

FL420 - 11 - add code below

Wattage	Colour Temperature	Beam Angle	Dimming	Additions
3	W	38	R	EM
3 - 10W 4 - 12W	W - 1800K - 3000K	15 - 15° 24 - 24° 38 - 38° 60 - 60°	R - Mains Dim	EM - 3 Hour EM



30, 60 and 90 Minutes Fire Rated



IP20 Rated



Insulation coverable



Unified Glare Rating



Mains, 0-10V & DALI Dimmable



Colour Rendering Index



7 Year Domestic & 5 Year Commercial Extended Warranty