

IRIS

Antiglare Plaster In - Black on Black



FX
ARC SERIES



Baffle Colour Selection

Choose from additional Gold or Silver Baffle covers

Easy Installation

Mains Loop-in and Loop-out Driver feature on Standard & Mains Dimmable Models

High CRI & Antiglare

A set back reflector for a low glare rating coupled with a powerful & Crisp light engine to help enhance the appearance of colours & objects

Description

The IRIS Antiglare is our versatile and yet elegant Fire Rated LED Downlight, featuring a multitude of Power Outputs, Kelvin and Dimming Protocol variations. This unit has been designed with Antiglare at the forefront of its design with its set back reflector, offering a UGR of only 11 when ordered with a black insert and 19 in standard white; producing a low glare and superior visual comfort. At a Colour rendering Index (CRI) of 95+ the IRIS offers a crisp light in any output which in turn enhances the appearance of colours and objects it comes into contact with.

Dimensions

Height: 75.5mm, 89mm (including Plaster In fixture)
Diameter: 80mm
Cut Out: 90mm

Wattage	10W	12W	13W
Lumen Output	650lm	780lm	845lm
Lumens per Watt	65lm/w		
Finish	RAL 9003		
Class	Class 3		

Part code Builder

FL410P - 11 - add code below

Wattage	Colour Temperature	Beam Angle	Dimming	Additions
3	G	4	S	EM
3 - 10W 4 - 12W 5 - 13W	G - 2700K C - 3000K N - 4000K	4 - 40°	S - Switched R - Mains Dim Z - 0 to 10V D - DALI	EM - 3 Hour EM EMD - 3 Hour EM DALI



30, 60 and 90 Minutes Fire Rated



IP65 Rated, suitable for bathroom Zones 1, 2 & 3



Insulation coverable



Unified Glare Rating



Mains, 0-10V & DALI Dimmable



Colour Rendering Index



7 Year Domestic & 5 Year Commercial Extended Warranty