

ARC Tilt

Modular - Plaster In White on White



FX

ARC SERIES



Baffle Colour Selection

Choose from additional Black Baffle covers

Easy Installation

Mains Loop-in and Loop-out Driver feature on Standard & Mains Dimmable Models

High CRI & High Efficiency

Featuring the latest Technology in LED engines to help enhance the appearance of colours & objects whilst offering high lumen efficiencies

Description

The ARC modular offers a modern minimalist design with its curved, smooth edges, allowing it to seamlessly blend into any environment. This versatile yet elegant Fire Rated LED Downlight features a multitude of power outputs, dimming protocols and Kelvin variations including Dim to Warm. As with all our modular range this unit features a high Colour Rendering Index (CRI) of 95+, offering a clean light in any output which in turn enhances the appearance of colours and objects it comes into contact with.

Dimensions

Height: 67mm
Diameter: Ø80mm
Cut Out: Ø68-70mm

| | | |
|-----------------|----------|--------|
| Wattage | 10W | 12W |
| Lumen Output | 850lm | 1020lm |
| Lumens per Watt | 85lm/w | |
| Finish | RAL 9003 | |
| Class | Class 3 | |

Part code Builder

FL530P - 00 - add code below

| Wattage | Colour Temperature | Beam Angle | Dimming | Additions |
|--------------------|-------------------------------------|----------------------------------------------|-----------------------------------------------------------|----------------------------------------|
| 3 | G | 15 | S | EM |
| 3 - 10W 4 - 12W | G - 2700K C - 3000K N - 4000K | 15 - 15° 24 - 24° 38 - 38° 60 - 60° | S - Switched R - Mains Dim Z - 0 to 10V D - DALI | EM - 3 Hour EM EMD - 3 Hour EM DALI |



30, 60 and 90 Minutes Fire Rated



IP20 Rated



Insulation coverable



Unified Glare Rating



Mains, 0-10V & DALI Dimmable



Colour Rendering Index



7 Year Domestic & 5 Year Commercial Extended Warranty