

# ARC Tilt

Modular - Plaster In White on Black Honeycomb



FX  
ARC SERIES



### Baffle Colour Selection

Choose from additional White Baffle covers

### Easy Installation

Mains Loop-in and Loop-out Driver feature on Standard & Mains Dimmable Models

### High CRI & High Efficiency

Featuring the latest Technology in LED engines to help enhance the appearance of colours & objects whilst offering high lumen efficiencies

### Description

The ARC modular offers a modern minimalist design with its curved, smooth edges, allowing it to seamlessly blend into any environment. This versatile yet elegant Fire Rated LED Downlight features a multitude of power outputs, dimming protocols and Kelvin variations including Dim to Warm. As with all our modular range this unit features a high Colour Rendering Index (CRI) of 95+, offering a clean light in any output which in turn enhances the appearance of colours and objects it comes into contact with.

### Dimensions

Height: 67mm  
Diameter: Ø80mm  
Cut Out: Ø68-70mm

Wattage	10W	12W
Lumen Output	850lm	1020lm
Lumens per Watt	85lm/w	
Finish	RAL 9003 and RAL 9005	
Class	Class 3	

### Part code Builder

**FL530P - 01H** - add code below

Wattage	Colour Temperature	Beam Angle	Dimming	Additions
<b>3</b>	<b>G</b>	<b>15</b>	<b>S</b>	<b>EM</b>
3 - 10W 4 - 12W	G - 2700K C - 3000K N - 4000K	15 - 15° 24 - 24° 38 - 38° 60 - 60°	S - Switched R - Mains Dim Z - 0 to 10V D - DALI	EM - 3 Hour EM EMD - 3 Hour EM DALI



30, 60 and 90 Minutes Fire Rated



IP20 Rated



Insulation coverable



Unified Glare Rating



Mains, 0-10V & DALI Dimmable



Colour Rendering Index



7 Year Domestic & 5 Year Commercial Extended Warranty