

# ICON

## GU10 Tilt Trimless Downlight - Black on Black



FX

GU10 SERIES



### Easy Access Housing

Removable twist and lock system allowing for easy lamp access

### Easy Installation

Loop in and out push in fast connector

### Low Profile

Constructed using fire rated glass allowing for a low profile and improved lamp ventilation

### Description

Our Icon GU10 offers a modern minimalist design that naturally blends into any environment. Pressed in steel and composed of fire rated glass allows this unit to have a very low profile, making it quick and easy to install, whilst offering improved ventilation to your LED bulb and in turn improving its lifespan.

### Dimensions

Cut Out: Ø80mm

Diameter: Ø74mm

Height: 50mm

Plaster In frame: Ø106mm x 87mm

Light Source	LED GU10
Wattage	7W Max
Lamp included	No
Finish	RAL 9005
Class	Class 2
Product Reference	<b>FD04PT-11</b>

### Optional Extras

The Insulation Guard allows this product to be covered by thermal and acoustic insulation e.g. loft insulation. Not suitable for blown insulation. Please ensure a max wattage of 7W when covering with insulation and utilising the insulation bracket.

Insulation Guard Reference: IC03



30, 60 and 90 Minutes Fire Rated



IP65 Rated, suitable for bathroom Zones 1, 2 & 3



Insulation Coverable when an Insulation Guard is installed



230V Mains Voltage powered



Mains Dimmable when a suitable lamp is installed



7 Year Domestic & 5 Year Commercial Extended Warranty