

# ARCO

## GU10 Tilt Downlight - White on White



FX

GU10 SERIES



### Easy Access Housing

Push in and push out lock system allowing for easy lamp access

### Easy Installation

Loop in and out push in fast connector

### Low Profile

Constructed using fire rated glass allowing for a low profile and improved lamp ventilation

### Description

Our Arco GU10 presents a classic architectural design that naturally elevates the style of any environment it sits in. Pressed in steel and composed of fire rated glass allows this unit to have a very low profile, making it quick and easy to install, whilst offering improved ventilation to your LED bulb and in turn improving its lifespan.

### Dimensions

Cut Out: Ø68mm  
Diameter: Ø75mm  
Height: 45mm

Light Source	LED GU10
Wattage	7W Max
Lamp included	No
Finish	RAL 9003
Class	Class 2
Product Reference	<b>FD05T-00</b>

### Optional Extras

The Insulation Guard allows this product to be covered by thermal and acoustic insulation e.g. loft insulation. Not suitable for blown insulation. Please ensure a max wattage of 7W when covering with insulation and utilising the insulation bracket.

Code: IC05



30, 60 and 90 Minutes Fire Rated



IP20 Rated



Insulation Coverable when an Insulation Guard is installed



Mains Voltage powered



Mains Dimmable when a suitable lamp is installed



7 Year Domestic & 5 Year Commercial Extended Warranty